

**2610+**  
High performance  
at low cost

**2 YEARS**  
ON-SITE  
WARRANTY



#### HIGHLIGHTS AT A GLANCE

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 24 wires printhead for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- USB Host interface for easy firmware-update
- Userfriendly, backlight illuminated LC display

# 2610+

The new Tally Dascom 2610+ is the **further developed variant** of the successful Tally Dascom 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 15 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB, Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only **up to 20% faster**, but also allows for a **noise reduction of up to 2 decibels** thanks to its design.

## TECHNICAL DATA

<b>Print speed</b>	683 cps (Fastest Draft); 600 cps (HS-Draft), 513 cps (Draft), 114 cps (LQ) bei 10 cpi
<b>Resolution</b>	Up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	457 pages per hour
<b>Character density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead lifetime</b>	500 Mio. impact per wire
<b>RAM</b>	256 kB
<b>Interface Standard</b>	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6) USB Host
<b>Interface Optional</b>	Serial RS-232
<b>Administration</b>	Tally WebPanel via Ethernet; Config-Tool via USB/Parallel
<b>Emulations Standard</b>	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9-Nadel Emulation
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
<b>Consummables</b>	Ribbon: 15 Mio. characters
<b>Paper handling Standard</b>	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
<b>Papier handling Optional</b>	Additional push tractor (rear)
<b>Copies</b>	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies
<b>Paper types</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper weight</b>	60-120 g/m <sup>2</sup>
<b>Paper format</b>	Width: 76 to 420 mm; Length: 76 to 599 mm
<b>Weight</b>	10,6 kg
<b>Dimensions</b>	600 x 265 x 200 mm (W x D x H)
<b>Noise</b>	<53 dB(A)
<b>Voltage</b>	100 - 240 V autosensing
<b>Power consumption</b>	60 Watt printing; <3 W Sleep Mode
<b>Temperature</b>	+10° to +40° C; 10% to 85% rel. humidity
<b>Print volume</b>	20.000 pages per month
<b>MTBF</b>	20.000 hours
<b>Driver</b>	Windows 7/8/10 and Server 2008/2012 (32/64 Bit); SAP

### Configuration:

- 2610+      Standard model

**DASCOM GB Ltd**  
Hart House, Priestley Road  
Basingstoke | Hampshire RG24 9PU | ENGLAND  
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400  
info.gb@dascom-com | www.dascom.co.uk

**DASCOM Europe GmbH**  
Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

**DASCOM (Holdings) LTD.**  
R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047