

## LA48N, LA48W



*Tally*

The narrow-carriage LA48N and wide-carriage LA48W are designed for a broad spectrum of applications and are specially optimized for the DEC® environment. There's support for DEC®ANSI, IBM® ProPrinter® X24e, and Epson® ESC/P2 emulation.

The 24-pin print head produces clear, crisp output of texts and graphics. The printer has nineteen resident fonts and eight resident bar code fonts ensuring fast, high quality text and dependable bar code printing.

### Highlights at a glance:

- Print speeds up to 400cps (LA48N) or 448cps (LA48W)
- 24-pin print head for clear, crisp output of text and graphics
- Standard parallel and serial interface
- Print head protection
- Auto interface switching on multiple I/F version
- Quiet operation

The printer offers simple switching of paper types and auto tear-off functionality. Parking continuous forms makes it easy to switch between continuous forms and single sheets. Continuous forms are automatically fed up to the tear-off position at the end of each job.

With a maximum noise level of only 49 dB(A) the LA48N and LA48W are very quiet printers compared with many competitive models.

### Configurations:

- **LA48N** 80 columns
- **LA48W** 136 columns

## LA48N, LA48W

<b>Print Speed</b>	480 cps (Fastest Draft); 360 cps (Draft), 113 cps (LQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	319 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 18, 20 cpi
<b>Line Density</b>	1, 2, 3, 4, 6, 7, 8 lpi
<b>Printhead Life</b>	400 million strokes
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and Serial RS-232
<b>Standard Emulation</b>	DEC ANSI PPL2, IBM ProPrinter, Epson ESC P/2
<b>Fonts</b>	Courier, Prestige, Elite, Boldface, Compressed, Draft, HS Draft, Correspondence Pica, Nimburs Sans®, Timeliess, OCR-A/B, 8 Barcodes
<b>Consumables</b>	Ribbon: 4 million characters
<b>Standard Paper Handling</b>	Push tractor and cut sheet insertion
<b>Number of Copies</b>	1 original + 5 copies
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 102 to 267 mm; Length: 76 to 364 mm (LA48N) Width: 102 to 420 mm; Length: 76 to 420 mm (LA48W)
<b>Physical Weight</b>	7,3 kg (LA48N) 9,7 kg (LA48W)
<b>Physical Size</b>	415 x 330 x 120 mm (W x D x H) (LA48N) 570 x 330 x 120 mm (W x D x H) (LA48W)
<b>Acoustic</b>	49 dB(A)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	10 Watt Stand-By
<b>Temperature</b>	+5° to +35° C; 20% to 80% humidity
<b>Workload</b>	8.000 pages per month
<b>MTBF</b>	20.000 hours

### DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 355130 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

Mantenimiento Periféricos Informáticos C/Canteras, 15 28860 Paracuellos de Jarama (Madrid) Tel: 00 34 91 7481604 Web: <https://mpi.com.es/>

Copyright © 2014 DASCOM Europe GmbH, Ver. 1 | January 2014

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 