

LEXMARKTM

Forms Printer 4227 plus

The Lexmark dot matrix printing family, a decades-long tradition of leading-edge engineering and value.



Technical Specifications

| | 238x plus | 239x plus | 4227 plus | |
|------------------------------|---|---|---|--|
| Models | 2380 plus : Narrow Carriage 2380-S03 plus : Passbook Printer 2381 plusS : Wide Carriage | 2390 plus : Narrow Carriage 2391 plus : Wide Carriage | Forms printer | |
| Technology | 9-pin dot matrix | 24-pin dot matrix | 9-pin dot matrix | |
| Maximum Print Line | 2380 plus : 8 in. / 203.2 mm 2381 plus : 13.6 in. / 345.4 mm | 2390 plus : 8 in. / 203.2 mm 2391 plus : 13.6 in. / 345.4 mm | 13.6 in. / 345.4 mm | |
| Print Speed | Up to 350 cps in FastDraft Up to 270 cps in Draft Up to 67.5 cps in Near Letter Quality | Up to 300 cps in FastDraft Up to 210 cps in Draft Up to 70 cps in Near Letter Quality | Up to 720 cps in FastDraft Up to 600 cps in Draft Up to 150 cps in Near Letter Quality | |
| Resolution | 240 x 144 dots per inch | 360 x 360 dots per inch | 40 x 144 dots per inch | |
| Memory (Print Buffer) | 11K standard expandable to 43 K | 64 K | 60K | |
| Compatibility | IBM PPS II, IBM ProPrinter III, III XL, Epson FX-850/1150 | IBM PPS II, IBM PS/1, 2390, IBM ProPrinter 24P, IBM PS/1 2205, IBM Proprinter X24E/XL24E, IBM Execlet, Epson LQ-850/1050 | IBM PPDS, Epson DFX-5000, Euro | |
| Fonts Selection | Gothic, Courier, Draft, FastDraft | Gothic, Courier, Prestige, Presentor, Orator, Draft, FastDraft | Gothic, Courier, Draft, FastDraft | |
| Paper Handling | Up to 6 part forms in variable lengths : 3in. / 76 mm to 22 in. / 558.9 mm Supports continuous forms, cut sheets, labels and envelopes | Up to 4 part forms in variable lengths : 3in. / 76 mm to 22 in. / 558.9 mm Supports continuous forms, cut sheets, labels and envelopes | Auto-gap Printhead; Up to 8 part forms in variable lengths : 3in. / 76 mm to 22 in. / 558.9 mm Supports continuous forms, cut sheets, labels and envelopes | |
| Size (WxDxH) / Weight | 2380 plus : 476.5x286.5x190.5 mm / 7.2 kg 2381 plus : 618.5x286.5x190.5 mm / 9.3 kg | 2390 plus : 476.5x286.5x190.5 mm / 7.2 kg 2391 plus : 618.5x286.5x190.5 mm / 9.3 kg | 618.5x286.5x275 mm 15.6 kg | |
| | 23xx plus | | 4227 plus | |
| Bar Code Fonts | Code 39, Code 128, EAN 8, EAN 13, Interleaved 2 of 5, UPC-A, POSTNET | | | |
| Paper Paths | Continuous forms may be loaded in either push or pull modes with the movable tractor feed or fed through the bottom feed; Automatic sheet feed option available which may be used in conjunction with continuous forms; Tractor 2 feeder option allows simultaneous loading of two continuous forms and forms selections with the touch of a button; | | Continuous Forms are loaded in the tractor feed; Cut sheets / envelopes / forms can be loaded in the front manual cut sheet tray; Tractor 2 feeder option allows simultaneous loading of two continuous forms and forms plus cut sheets and forms selections with the touch of a button; | |
| Ease of Use Features | Four panel selectable forms macros; Automatic top-of-form alignment panel selectable forms macros | | LCD operator panel; 7 resident bar codes; Four panel selectable forms macros | |
| Printhead Life | 200 million wire fire per wire | | 400 million characters | |
| Ribbon Yield | 4 million characters in Draft Mode | | 15 million characters in Draft Mode | |
| Acoustics | 55dBa in Courier Mode; 52 dBa in Quiet Mode with Acoustic Option | | 55dBa in Courier Mode | |
| Supplies | Lexmark Auto-inking® Ribbon : PN 1040930 | | Ribbon : PN 13L0034 | |
| Reliability | 10,000 power-on-hours MTBF at 25% duty cycle | | 10,000 power-on-hours MTBF at 50% duty cycle | |
| Electrical | 220/240 Volt AC (50Hz); Energy Star compliant | | | |
| Interface | Parallel interface setting with standard Centronics protocol; RS232/422 Serial Optional | | Parallel interface setting with standard Centronics parallel port; Serial RS232 / RS422 IEEE 1284 compliant Automatic Interface Switching between serial and parallel | |
| Options | PN 11A3195 : Tractor 2 Feeder (2380/2390 plus) PN 11A3265 : Tractor 2 Feeder (2381/2391 plus) PN 79F4840 : Automatic Sheet Feed (2380/2390 plus) PN 11A3097 : " " (2381/2391 plus) PN 1332972 : Acoustic Shield (2380/2390 plus) PN 1332973 : Acoustic Shield (2380/2390 plus) PN 1180727 : 32K (Download Buffer) (2380/2381 plus) PN 1180859 : Extended Cut Sheet Guides PN 1368700 : Serial Adapter PN 11A6276 : Coax PN 11A6277 : Twinax MarkNet™ Pro for Token Ring and Ethernet | | PN 11A6196 : Tractor 2 Feeder PN 11A3097 : Automatic Sheet Feed PN 1180727 : 32K (Download Buffer) PN 1180725 : 32K non volatile download font memory PN 1329605 : Parallel cable (3m - standard) PN 1427498 : Parallel cable (6m - long) PN 11A6276 : Coax (SCS Only) PN 11A6277 : Twinax (SCS Only) Ethernet (Via External Network adapter) support MarkNet Pro for Ethernet | |
| Warranty | One-Year on-site | | | |
| Optional | 1-, 2-, 3-, or 4-Year extended Warranties available | | | |

