

The Bridge to Lineprinter

« Fast and Efficient »



The already well established models in the market for years as PSi PP 407 and PSi PP 408 with the integrated cutting function served as a basis for the performance tuning. The result is: the two new models PP 407 LPM and PP 408 LPM. Thanks tuning the PSi LPM printing models get now to a printing speed up to 470 lines per minute at a line length of 60 characters. PSi Matrix not only closed the gap to the line printers but even surpasses them in speed in certain applications.

The demand for matrix printers with even higher print speed comes first of all from the areas **transport logistics** where loading lists and accompanying documents have to be printed as fast as possible, so that no waiting times arise for the drivers, and furthermore in **automotive industry** where printouts have to run synchronously in time with predetermined cycle times on assembly lines.

A further highlight of the PSi PP 408 LMP printer is the integrated cutting function which allows to separate print jobs or to cut each page to optimize post-processing as best as possible.

- Ruggedized heavy duty 24-wire dot matrix printer
- Max. Performance:
 - 920 characters per second
 - up to 565 lines per minute
 - up to 830 pages per hour
- Plug & Print:
 - 2 Plug-in tractor cassettes for easy paper loading for multiple job handling
- Flatbed technology for reliable and straight paper transport
- Automatic Gap Control (AGC)
- 1 + 5 excellent copies
- 14 fonts including Box Characters; 13 barcodes
- Uni- and bidirectional printing
- Long life ribbon up to 30 million characters
- Optional Silent-Kit for additional noise reduction of ~75%
- Integrated cutter in the Model PP 408 LPM
- Typical print volume 40.000 pages per month

TECHNICAL DATA

Printer Specification

Technology:	serial impact dot matrix
Printhead:	24 wires, 0.25 mm (0.01 inch) needle diameter; life time 400 million characters
Print mode:	Data (DQ), Near Letter (NLQ) and Letter Quality (LQ)
Print format:	136 characters at 10 cpi
Ribbon:	XXL nylon ribbon cassette, black (up to 30 million characters)
Dimensions:	740 x 370 x 325 mm (WxDxH) (29.6 x 14.8 x 13 inches)
Weight:	~ 28.5 kg (62 lb)
Diagnostics:	elftest, hexdump, remote diagnostics via interface
Operator Panel:	16 digit LCD display, trilingual (German, English, French)
Rated voltage:	200-240 V, 50-60 Hz (optionally 100-125 V, 50-60 Hz)
Power input:	120 W, 20 W standby
Environmental temperature:	operating: +10 to +35 °C (+50 to +95°F) 20 to 80% rel. humidity storage: -40 to +70 °C (-40 to +158°F) 5 to 85% rel. humidity
Noise level:	55 dB(A) acc. to ISO 7779
Agency approvals:	VDE/GS, UL, C-UL, CE, FCC-B

Performance

Print speed:	Acceleration = 6g, NFQ = 2400 Hz with HSD 92.0 ips
(at 10 cpi)	mode cps: mode lpm:
	HSD: 920 HSD: 40 characters per line 565
	DRAFT: 767 HSD: 60 characters per line 467
	NLQ: 383 HSD: 80 characters per line 404
	LQ: 192
Throughput:	mode:
(ECMA 132,	HSD: 830 pages per hour
letter, 1-ply)	DRAFT: 795 pages per hour
fanfold (at 10 cpi)	NLQ: 560 pages per hour
	LQ: 320 pages per hour
Duty cycle:	typical 40.000 pages per month
MTBF:	10.000 hours at 30% load

Paper Handling

Paper paths:	flatbed technology, 2 inputs for fanfold paper, 1 output for fanfold paper, paper path selectable via software or operator panel
Paper input:	two independent, easy to plug-in tractor cassettes for fanfold paper; push tractor with park position
Paper output:	PP 407: to the rear with zero tear-off PP 408: (integrated cutter) cutted sections to the top and continuous or cutted sections to the rear,
Paper weight:	formsets up to 350 g/ m ² (14 oz/ m ²), 60 to 90 g/ m ² (2.4 to 3.6 oz/ m ²) per sheet; single-layer up to 240 g/ m ²
Paper width:	4 to 16 inch (100 to 400 mm)
Form feed speed:	20 inch/second; 25 ms per line feed
Automatic GAP Control (AGC):	optimizes automatically the distance between print head and paper according to paper thickness
Paper run control:	allows unattended printer operation
Copies:	1 original + 5 copies, maximum paper thickness 0.5 mm (0.02 inch)

Connectivity

Interfaces:	parallel IEEE 1284, serial RS-232 (DSUB 9), USB 2.0
Emulations:	IBM Proprinter XL24 (AGM), Epson LQ 2550/1060, ESC/P2
Buffer:	selectable up to 176 KByte
Character sets:	ISO 8859/1, ISO 8859/9, 8859/15; IBM Set 1/Set 2 in 14 national versions; IBM Code Pages 437, 850, 852, 857, 858, 860, 863, 865; Epson Ext. Char. Set in 15 national versions; Eastern European character sets 771, 773, 774, 775, 1125, 1251; Baltic RIM, Greek, CZ, HUN, Russia, Win Lat 2
Fonts:	Draft quality: Data and Data Large; Near letter and letter quality: Courier, OCR-A, OCR-B, Orator, Prestige, Roman, Script, Sans serif
Character attributes:	bold, italic, shadow, outline, double strike, underline, double underline, overline, strike through, sub/superscript, double to octuple, for Data Large 99-fold size
Pitches:	10, 12, 15, 17.1, 18 and 20 cpi, proportional
Line spacing:	2, 3, 4, 6, 8, ... 360 lpi
Barcode:	EAN 8, EAN 13, UPC-A, UPC-E, Postnet, KIX Code, Code 39, Code 93, Code 128 (incl. EAN 128), Codabar, 2 of 5 industrial, 2 of 5 interleaved, and MSI Mod 10/10 (horizontal or vertical)
Graphics:	360 x 360 dpi max. (uni-/ bidirectional)
Macros:	parameter settings for up to four individual printer configurations, selectable via software or operator panel

PERSONALITY MODULES

Emulations / Interface	
IBM/Epson:	Serial/Parallel/USB or Serial/Ethernet/USB
IPDS:	Ethernet
IBM-IGP 10/20/40:	Parallel or Ethernet
HP 2934/2235:	Serial/Parallel/USB or Serial/Ethernet/USB
Genicom:	Serial/Parallel/USB or Serial/Ethernet/USB
Stringchange:	Parallel or Ethernet

Printer drivers for Windows and SAP R/3 device types are available for download at <http://www.psi-matrix.eu>

Options

Tractor Cassette:	Additional tractor cassettes for quick exchange of loaded media.
Printer Stand:	Dimensions: 635 x 660 x 840 mm (WxDxH), weight: approx. 25 kg (55 lb)
Stacker Option:	System to be integrated into the stand for orderly stacking of fanfold paper, capacity: ~ 2.000 pages
Sound Cover:	For an optimal sound insulation in application with the Printer Stand, dimensions: 910 x 575 x 420 mm (WxDxH), weight: approx. 33 kg
Sound Cabinet:	Replacement of Printer Stand and Sound Cover, dimensions: 900 x 715 x 1.150 mm (WxDxH), weight: approx. 80 kg
Sound reduction kit:	To reduce the noise level by 75 %

This is only an extract of the product specification. For a detailed specification it is referred to the comprehensive product documentation. Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

PSi Matrix GmbH

Homeswiese 116a
57258 Freudenberg, Germany
Tel: 02734 284 77 500 e-mail: sales@psi-matrix.eu
Fax: 02734 284 77 599 Internet: www.psi-matrix.eu

professional printing solutions

