

F26C

Ideal for:

- Labels and tickets
- Full color label production on-demand
- > Business and workflow documents

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- > Handles continuous form and cut-sheet media
- Reliable paper transportation via tractor feeding
- > Automatic job separation with integrated cutter
- > USB 2.0, Ethernet (10/100 Mbit) as standard
- > Movable tractor unit

ECONOMICAL COLOR LASER PRINTING FOR SMALL PRINT VOLUMES

F26C

No matter if printing single sheets or continuous form media, whether color labels and tickets or eye-catching business presentations – for all smaller batch print run needs requiring color, the Microplex F26C is the flexible, fast and extremely reliable and very economical solution. And a further benefit: the F26C is quiet and easy to use. For smaller materials up to 8.5 inch the Microplex F26C is the best choice.

F26C

SPECIFICATIONS



Print technology

Print Engine

Processor Print speed Color

Print resolution Duty cycle Power supply Power consumption Acoustic noise Dimensions (WxDxH in mm) Weight **Environment temperature Relative humidity** Interfaces

Memory

Emulations

PCL5c via windows driver

LED, OPC heat/pressure fixing 533 MHz CPU up to 26 pages/minute (A4 Portrait) 7,7 m/min (A4 Portrait) max. 1.200 dpi x 600 dpi max. 20.000 pages 220-240 V / 50 Hz, 600 W <37 / <54 dB (A) 430 x 790 x 450 45 kg (without options) 10 - 32°C 20 - 80 % (rel., non-condensing) Serial: USB 2.0 Parallel: IEEE 1284 (Centronics) LAN: Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP) RAM: 256 MB Optional: max. 768 MB SDHC Memory Card: 16 GB



Printable Media


Size

0,5"-52"(12,7mm-1320mm) Form length Form width 5" - 8,5" (120mm-215mm) (Incl sprocket holes Printable area 8" (203mm)

Weight

Continuous media: Cutsheet tray:

64 - 250 g/m² 64 - 220 g/m²



Paper Path

Input

Continuous Cutsheet

push tractor 530 sheets (A5, A4, B5)

Output Continuous Cutsheet

Face up 500 sheets, Face-Down

Microplex Printware AG Panzerstraße 5 | 26316 Varel | Germany phone +49 4451 91 37-0 | fax +49 4451 91 37-49



The brand names referred to are the registered trademarks of the re-spective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 21.11.2016

PRINTING TECHNOLOGIES