T2250

Tally

Highlights at a glance:

- Print speeds **up to 720 cps**
- **26,000 pages per month** workload
- 136 columns
- 24 pin print head produces excellent print quality
- **Automatic gap adjustment** and quick tear
- **Straight through paper path** for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

The T2250 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 53 dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Configurations:
- **T2250** Standard Product
- **T2250 IGP** with IGP/PJL Support

CORTADO Cloud Printing Ready

DASCOM® MPI

SOLUTIONS FOR BUSINESS PRINTING

T2250

Print Speed	720 cps (Fastest Draft); 600 cps (Draft), 270 cps (DPQ), 180 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	482 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	400 million characters
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and serial RS232
Optional Connectivity	Serial Current Loop (20mA), Ethernet 10/100BaseT
Standard Emulation	IBM ProPrinter XL24, Epson LQ2250, MTPL + Barcode + LCP **IGP Version**: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Optional Emulation	DEC LA 75, ECMA 9011, MT50
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and large character printing
Consumables	Ribbon: 5 million characters
Standard Paper Handling	Push tractor and friction (front), continuous paper with straight paper path, cut sheet front insertion, tear off and park position
Optional Paper Handling	Additional push tractorn (front), additional push tractor (rear), Automatic sheet feeder rear (100 sheets) or front (50 sheets),
Number of Copies	Push tractor front: 1 original + 5 copies; Push tractor rear: 1 original + 1 copy; Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m²
Paper Size	Width: 76 to 420 mm; Length: 76 to 599 mm
Physical Weight	13,2 kg
Physical Size	600 x 300 x 295 mm (W x D x H)
Acoustic	53 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	40 Watt Printing; <10 W Sleep Mode
Temperature	+10° to +35° C; 20% to 80% humidity
Workload	26.000 pages per month
MTBF	20.000 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008; SAP

DASCOM GB Limited
Hart House, Priestley Road
Basingstoke, Hampshire RG24 9PU
Tel: +44 1256 355130 – Fax: +44 1256 481400
info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
FLATBED PRINTERS
THERMAL PRINTERS

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.
Copyright © 2014 DASCOM Europe GmbH, Ver. 1, January 2014

Mantenimiento Periféricos Informaticos C/Canteras, 15 28860 Paracauellos de Jarama (Madrid) Tel: 00 34 917481604 Web: https://mpi.com.es/