

# PREMIUM COATED DIRECT THERMAL LABEL

A Premium, top-coated, direct thermal labelstock offering enhanced image protection for challenging environments. Permanent, rubber hotmelt adhesive that adheres well to a wide range of substrates and performs well at low temperatures

## RECOMMENDED APPLICATIONS:

- Food
- Retail
- Logistics
- Inventory
- Tags
- Conveyor sorting

## ADHESIVE SPECIFICATIONS:

- Permanent, Rubber Hotmelt
- Tack min: 12 N
- PE-looptack min: 10 N
- Tensile strength: 4.5 kN/m (MD), 1.8 kN/m (CD)
- Minimum application temperature: 0°C
- Service temperature: -40°C to +60°C

## LINER SPECIFICATIONS:

- Yellow, transparent glassine
- Grammage: 45 g/sqm
- Caliper: 44 µm

## COMPLIANCE:

- EC Food contact EC 1935/2004, EU 10/2011
- BfR XXXVI for direct contact with dry and/or greasy food (Face and Backing)
- FDA 21 CFR 175.105 (Adhesives)
- Quality Control Approved
- PEFC



## Why choose Genuine Printronic Auto ID Supplies?

### *Guaranteed Quality*

Genuine Printronic Auto ID Supplies are manufactured to strict quality standards to ensure optimum performance and user satisfaction.

### *Guaranteed Compatibility*

From core to cut, Genuine Printronic Auto ID Supplies are designed to work flawlessly through your Printronic Auto ID printer.

### *Consistent Performance*

From the first label to the last and from one order to the next, Genuine Printronic Auto ID Supplies will provide clear, crisp imaging and consistent performance.

### *"No Worry" Reliability*

Printronic Auto ID quality control, manufacturing and component standards ensure "No Worry" reliability.