

UNCOATED DIRECT THERMAL LABEL

A general purpose, non-topcoated, direct thermal labelstock with good imaging characteristics. Suitable for shorter term applications in retail and logistics. High-tack, permanent, acrylic adhesive that adheres well to a wide range of substrates.

RECOMMENDED APPLICATIONS:

- Logistics
- Inventory
- Tags
- Conveyor sorting
- Food Contact
- Retail

ADHESIVE SPECIFICATIONS:

- Permanent, Acrylic adhesive
- Tack min: 14 N
- PE-looptack min: 10 N
- Minimum application temperature: 0°C
- Service temperature: 0°C to +80°C

LINER SPECIFICATIONS:

- Yellow, transparent glassine
- Grammage: 48 g/sqm
- Caliper: 44 µm

COMPLIANCE:

- BfR XXXVI for direct contact with dry and/or greasy food (Face and Backing)
- FDA 21 CFR 175.105 (Adhesives)
- Quality Control Approved
- PEFC



Why choose Genuine Printronix Auto ID Supplies?

Guaranteed Quality

Genuine Printronix Auto ID Supplies are manufactured to strict quality standards to ensure optimum performance and user satisfaction.

Guaranteed Compatibility

From core to cut, Genuine Printronix Auto ID Supplies are designed to work flawlessly through your Printronix Auto ID printer.

Consistent Performance

From the first label to the last and from one order to the next, Genuine Printronix Auto ID Supplies will provide clear, crisp imaging and consistent performance.

"No Worry" Reliability

Printronix Auto ID quality control, manufacturing and component standards ensure "No Worry" reliability.