

**NEW**

**MPI**  
CONTINUOUS FORM LASER PRINTER

**PP 4060 MICR 600dpi**

## Two-Up Fanfold MICR Printer



- Cost effective MICR printing at consistent high quality
- E13-B and CMC-7 MICR encoding with internal fonts
- 18 inch paper width (Two-Up for 8.5 inch wide cheques)
- High throughput of up to 14,000 cheques per hour
- Reliable print engine
- Automatic paper stacking with iPS 4050



**NEW**



# CONTINUOUS FORM LASER PRINTER

**PP 4060 MICR 600dpi**

## TECHNICAL DATA

### Printer Specification

**Print Speed:** up to 63 pages per minute (Letter Two-Up)  
up to 59 pages per minute (A4 Two-Up)  
up to 42 pages per minute (A4 landscape)  
up to 41 pages per minute (Letter landscape)  
up to 31 pages per minute (11" form length)  
up to 2,100 lines/minute at 6 lines/inch

up to 14,000 cheques per hour (3" x 8.5" cheques on 12" x 18" paper in Two-Up mode)

**Resolution:** 600 x 600 dpi

**Workload:** 300,000 pages per month

**Print Method:** Electrophotographic, LED array, organic photoconductor, 2 component toner/developer, heat and pressure roller system with adjustable fusing temperature

**Control Panel:** Four line LCD display (20 characters/line)  
Keys: On Line, Menu, Select, Return

**Diagnostics:** Selftest, hexdump

**Dimensions:** 890 mm x 350 mm x 780 mm (W x H x D) (inclusive tractor cassettes)

**Weight:** 246 lbs. (112 kg) consumables included, without iPS 4050

**Rated Voltage:** 100 - 110 V (-10/+6%) AC, 50 - 60 Hz  
110 - 120 V (-10/+6%) AC, 50 - 60 Hz  
220 - 240 V (-10/+6%) AC, 50 - 60 Hz

**Power Consumption:**  
Operating power < 1,200 W average (< 1,650 W peak)  
Operating current < 12 A average (< 15 A peak) 110 V  
Standby < 400 W  
Sleep mode < 45 W

**Environmental Conditions:**  
operating +15 to + 35°C, 30 to 50 % rel. humidity  
storage - 10 to + 40°C, 95 % rel. humidity (40°C)  
storage consumables - 10 to + 40°C, 95 % rel. humidity (40°C)

**Sound Level:** < 55 dB(A) operating

**Lifetime:** up to 18,000,000 pages

**Agency Approvals:** VDE / GS, UL, C-UL, CE, FCC

### Connectivity

**STANDARD INTERFACES AND EMULATIONS**

**Interfaces:** Parallel IEEE 1284,  
Ethernet 10Base/100BaseTX

**Emulations /PDL:** HP LaserJet 4 (PCL 5e, P JL), HP - GL/2  
PCL / P JL Extensions

**Fonts:** 45 scalable fonts, 10 bitmap fonts, E13-B, CMC-7

**Barcodes:** Code 39, Code 93, Code 128, Codabar, 2/5 industrial,  
2/5 interleaved, EAN 8/13 Add on 2/5, Postnet, MSI,  
UPC-A, UPC-E, KIX-Code, Datamatrix Code

### Paper Handling

**Type:** Continuous forms and labels with tractor pin holes

**Paper Transport:** Reversible paper motion, straight-through paper path

**Paper Input:** Two independent, detachable tractor cassettes for fanfold paper

**Paper Output:** directable to the rear (zero tear off or cut without loss of form)

**Paper Cutter:** Integrated cutting device separates print jobs, enables change of forms without operator involvement

**FANFOLD PAPER**

**Paper Width:** min. 6 inch, max. 18 inch (print area 17 inch)  
**Paper Length:** min. 3 inch, max. 24 inch  
min. 7 inch, max. 17 inch (if attached to stacker)

**Weight:** 64 g/m<sup>2</sup> up to 155 g/m<sup>2</sup>

### Control Unit

**Processor:** PowerPC

**Data Memory:** 128 MB

**Program and Font Memory:** 32 MB FLASH EPROM  
allows onsite software update

**Stacker Control:** Supports attached intelligent Paper Stacker iPS 4050

### Consumables

**Toner Kit:** up to 1,6 Mio cheques at A4 page with 2% coverage and 4 cheques 3" x 8" per page

**Photoconductor:** up to 280,000 pages (A4 Two-Up)

**Developer:** up to 400,000 pages (A4 Two-Up)

**Fuser Unit:** up to 940,000 pages (A4 Two-Up)

### Options

**iPS 4050:** Assures accurate stacking of forms up to 3,000 pages without operator involvement

**Dimensions:** iPS: 1,060 x 860 x 670 mm (WxHxD)  
printer / iPS: 1,120 x 1,160 x 780 mm (WxHxD)

**Weight:** iPS 4050: 52 kg  
printer/iPS 4050: 164 kg

**Printer drivers for all common Windows operating systems are available. Printer configuration software and SAP R/3 Device Types can be loaded from the PSi Laser website.**

This is only an extract of the product specification. For a detailed specification it is referred to the comprehensive product documentation. Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

**PSi Laser GmbH**  
Homeswiese 116a  
D-57258 Freudenberg  
phone +49 (0)2734 28477-0 sales@psi-laser.de  
fax: +49 (0)2734 28477-300 web: www.psi-laser.com

**PSi Laser**  
Excellence in printing solutions

PP 4060MICR / 01.2011