



High quality, low cost, compact laser continuous forms printers that provide document sequence integrity and high throughput

INFOPRINT 75 AND INFOPRINT 100 LASER CONTINUOUS FORMS PRINTERS

ncom 1807

HIGHLIGHTS

- Production speeds up to 154 IPM.¹
- High quality 600 DPI output.
- Easy to use auto-loading pin-feed paper path.
- Standard internal powered output stacker.
- Small footprint (under 9 square feet or .84 square meters).
- Supports common printer data languages PostScript³ and PCL.²
- Broad range of service offerings including 7x24 coverage.
- ENERGY STAR® qualified.

InfoPrint 75 and InfoPrint 100 are new laser printers that provide the document sequence integrity of continuous forms printing in a compact footprint backed by around-the-clock service. For documents that must remain in page sequence, the InfoPrint 75 or InfoPrint 100 can print invoices, picking slips, labels or mailings with the high throughput of a continuous forms printer. These entry-level continuous forms printers feature ease of loading for box fanfold forms and easy unloading from a power stacker. The highly reliable tractor feed paper path can print forms formatted in 1-up landscape format or 2-up portrait format

with a simple adjustment in the paper path. The print speeds range from 75 impressions per minute up to 154 impressions per minute,¹ providing very efficient operation. Print output is at 600 DPI, providing superb clarity on text, graphics and sharply defined barcodes. The InfoPrint 75 and InfoPrint 100 are backed by InfoPrint Availability Services that can be tailored to your operating requirements. These printers are Energy Star Compliant and support an energy-efficient operation.



INFOPRINT 75 AND INFOPRINT 100 CONTINUOUS FORMS PRINTERS

Item	Specifications	
Print speed ¹	InfoPrint 75	InfoPrint 100
Linear feet/per minute	53.25	71
Linear meters/per minute	16.23	21.64
1-up Letter – Landscape	75 ipm	100 ipm
2-up 8.5" x 11"	116 ipm	154 ipm
1-up A4 Landscape	77 ipm	103 ipm
2-up A4	109 ipm	145 ipm
Media	InfoPrint 75 and InfoPrint 100	
Paper width	6.5" to 18" (165 mm to 457 mm)	
Paper weight	17 lb. to 42 lb. (64 gsm to 157 gsm)	
Paper length	6" to 14" (152 mm to 356 mm) 7" to 28" (178 mm to 712 mm)	
Paper types	Continuous tractor forms, tip-on cards and labels	
System attachments	Ethernet (10Base-T/100Base-TX/1000Base-T automatic switching), TCP/ IP (lpr, RawTCP), EtherTalk	
Software support	PostScript V3016 and PCL 5e: InfoPrint Solutions Company InfoPrint Manager for AIX® 4.2 and Windows 2.2 (PSF command and passthrough printer types only); InfoPrint ProcessDirector for AIX® V1.3.1 and InfoPrint ProcessDirector for Linux V1.3.1 (passthrough printer type only); IPDS availability planned for the first half of 2009 ³	



INFOPRINT 75 AND INFOPRINT 100 CONTINUOUS FORMS PRINTERS

Standard featuresResolution: 600 DPI, 512 MB memory
Power Stacker: 2000 sheets at 17#/65 gsm

Print Imaging Area characteristics (per engine)

Maximum Image Size (width) 17"

 Length
 35" (890 mm)

 Depth
 36/39" (905/985 mm)

 Height
 55" (1,383 mm)

 Weight
 792 lb. (360 kg)

Power requirements 200/240 VAC/50 Hz or 60 Hz single phase, 2 wires and grounding wire

Voltage determined by country standards

Environmental conditions

Permitted ranges Temperature: 61° to 89°F (16° to 32°C)

Relative humidity: 20% to 80% RH

Optimal ranges Temperature: 66° to 77°F (19° to 25°C)

Relative humidity: 30% to 65% RH

Acoustics 65 dBA (operating) or 50 dBA (idle)

Altitude 0 – 7,000 feet (0-2100 meters)

Cost-saving and environmental features ENERGY STAR® qualified

Exact speed varies depending on document complexity, system configuration, software application, driver, and printer state.

²Some forms may require testing prior to installation.

³IPDS availability is currently planned for the first half of 2009. As with any product in the development phase, problems may be identified in product and/or beta testing, which impacts planned availability or, in some cases, results in termination of the development activity. Contact your sales representative for details.





InfoPrint Solutions Company

FOR MORE INFORMATION

Contact your InfoPrint Solutions Company representative or InfoPrint Solutions Partner or visit:

infoprintprinters.com

© Copyright InfoPrint Solutions Company 2008. All rights reserved.

InfoPrint Solutions Company 6300 Diagonal Highway 002J Boulder, Colorado 80301-9270

Printed in the United States of America May 2008

Ricoh and the Ricoh logo are registered trademarks of Ricoh Co., Ltd. in Japan, other countries or both. IBM and the IBM logo are registered trademarks of International Business Machines Corporation in the United States, other countries, or both. The Ricoh and IBM trademarks are used under license from their respective trademark owners.

InfoPrint Solutions Company is a tradename of InfoPrint Solutions Company, LLC, in the United States, other countries, or both. InfoPrint is a registered trademark of Ricoh Co., Ltd., in the United States, other countries, or both. InfoPrint is used under license from the trademark owner.

References in this publication to InfoPrint Solutions Company products or services do not imply that InfoPrint Solutions Company intends to make them available in all countries in which InfoPrint Solutions Company operates. Any purchase of such products or services will be exclusively governed by the terms of the sales or license agreement applicable to such purchase to the maximum extent allowed by law.

These terms are trademarks or registered trademarks of Ricoh Co., Ltd., in the United States, other countries, or both: InfoPrint, IPDS and Ricoh.

These terms are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both: IBM, AIX and the IBM logo.

Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Other company, product, or service names may be trademarks or service marks of others.



IPD03043-USEN-01